



TEXICRYL[®] 13-307

Carboxylated acrylic copolymer emulsion

INTRODUCTION TEXICRYL 13-307 is an alkali soluble acrylic emulsion thickener.
TEXICRYL 13-307 is APEO free.

CHARACTERISTICS (Not to be taken as a specification)

Solids Content	%	30
Thickening test @ pH 7 - Brookfield Viscosity, Spindle 4, 10 rpm	mPa s	9.000
Viscosity at 25°C (Brookfield RVT, Spindle 2, 100 rpm)	mPa s	25
Particle size	nm	200
pH		2.5
Specific gravity at 25°C	g/cm ³	1.07
Minimum film formation temperature	°C	0
Glass transition temperature	°C	60

APPROVALS TEXICRYL 13-307 complies with the requirements of part 175.105 without limitation. TEXICRYL 13-307 complies with the requirements of parts 176.170, 176.180.

APPLICATIONS

TEXICRYL 13-307 can be used for thickening ceramic tile adhesives when structuring with clays is not appropriate. This product is slightly water sensitive so would not be used to thicken systems where class AA standard is required.

PACKAGING

TEXICRYL 13-307 is supplied in drums, 1 tonne IBC's or bulk supplies are delivered by road tanker.

STORAGE

TEXICRYL 13-307 may be stored in the containers in which it is supplied.

Protect from frost and extended exposure to direct sunlight.

HEALTH & SAFETY

Please see separate Material Safety Data Sheet.

Issue No.1

Scott Bader Company Limited
Wollaston, Wellingborough, Northamptonshire, NN29 7RL
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

