



# TEXIPOL<sup>®</sup> 67-5060

## Inverse Emulsion Polymer

### INTRODUCTION

**Texipol 67-5060** is a new multifunctional synthetic thickener, specifically designed for reactive, disperse and acid dye printing applications. **Texipol 67-5060** can be used in rotary and flat bed printing processes

### CHARACTERISTICS (Not to be taken as a specification)

Appearance		Creamy liquid
Viscosity at 25°C (Brookfield RVT, Spindle 6,10rpm)	mPa s	15000
2% aqueous solution viscosity (Brookfield RVT, Spindle 6,5rpm)	mPa s	35000
2% aqueous solution pH		5.3
Specific gravity at 25°C		1.05

**APPLICATIONS**

**Texipol 67-5060** has been designed to thicken acid, disperse and reactive printing paste formulations almost instantaneously. **Texipol 67-5060** produces prints of high definition with excellent colour yield, brightness and handle. **Texipol 67-5060** can be used in both the conventional and automatic colour kitchen methods. If required the product can be directly pumped and metered

**PACKAGING**

**Texipol 67-5060** is supplied in drums and IBC's.

**STORAGE**

**Texipol 67-5060** should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Exposure to frost should be avoided. Do not store in mild steel , Copper or Aluminium containers

**HEALTH & SAFETY**

Please see separate Material Safety Data Sheet.

Issue No.1

Scott Bader Company Limited  
Wollaston, Wellingborough, Northamptonshire, NN29 7RL  
Telephone: +44 (0) 1933 663100 Facsimile: +44 (0) 1933 666529

