



## SAFETY DATA SHEET TEXIPOL 67-5060

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME                    TEXIPOL 67-5060  
 PRODUCT NO.                    675060  
 SUPPLIER                         Scott Bader  
                                       Wollaston  
                                       Wellingborough  
                                       Northamptonshire. NN29 7RL  
                                       Tel: +44(0)1933 663100  
                                       Emergency (24 hours) +44(0)1933  
                                       663399  
                                       Fax: +44(0)1933 663693  
                                       E-mail: reach@scottbader.com

### 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

CLASSIFICATION (1999/45)        Not classified.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
ALCOHOL ETHOXYLATE		69011-36-5	2-4%	Xn;R22. Xi;R41.
Amides, C16-18 and C18-unsatd N,N-bis(hydroxyethyl)		68603-38-3	<1.5%	Xi;R38,R41.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	265-149-8	64742-47-8	25-30%	Xn;R65. R66.

The Full Text for all R-Phrases is Displayed in Section 16

#### COMPOSITION COMMENTS

Water based emulsion

### 4 FIRST-AID MEASURES

#### INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

#### INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

### 7 HANDLING AND STORAGE

**TEXIPOL 67-5060****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Protect from freezing and direct sunlight.

**STORAGE CLASS**

Chemical storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION****PROTECTIVE EQUIPMENT****ENGINEERING MEASURES**

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

**DO NOT SMOKE IN WORK AREA!** Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Viscous liquid
COLOUR	White / off-white
ODOUR	Mild or Ammonia
SOLUBILITY	Soluble in water.
BOILING POINT (°C)	50-150
RELATIVE DENSITY	1.05 @ 25 °C
pH-VALUE, CONC. SOLUTION	3-10
FLASH POINT (°C)	>100 CC (Closed cup).

**10 STABILITY AND REACTIVITY****STABILITY**

No particular stability concerns.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**11 TOXICOLOGICAL INFORMATION****INHALATION**

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

**INGESTION**

May cause discomfort if swallowed.

**SKIN CONTACT**

Liquid may irritate skin.

**EYE CONTACT**

Spray and vapour in the eyes may cause irritation and smarting.

**TEXIPOL 67-5060****12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

Not regarded as dangerous for the environment.

**13 DISPOSAL CONSIDERATIONS**

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not classified.
SEA TRANSPORT NOTES	Not classified.
AIR TRANSPORT NOTES	Not classified.

**15 REGULATORY INFORMATION**

## RISK PHRASES

NC	Not classified.
----	-----------------

## SAFETY PHRASES

P13	Safety data sheet available for professional user on request.
-----	---

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**16 OTHER INFORMATION**

REVISION DATE	18/08/2011
---------------	------------

REV. NO./REPL. SDS GENERATED	0
------------------------------	---

## RISK PHRASES IN FULL

R22	Harmful if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R41	Risk of serious damage to eyes.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.